



NOTES:

1. DESIGN & FAB. PER AWWA C-223
2. WORKING PRESSURE: 150 PSI
3. FINISH: FUSION EPOXY COAT
4. FASTENERS: 304 SS

THIS DRAWING INCLUDING ALL NOVEL AND PATENTED OR
PATENTABLE SUBJECT MATTER EMBODIES CONFIDENTIAL
INFORMATION OF JCM INDUSTRIES, INC. AND IS LOANED WITH
THE UNDERSTANDING THAT IT WILL NOT BE REPRODUCED
NOR BE USED FOR ANY PURPOSE EXCEPT FOR WHICH LOANED
UNLESS WRITTEN PERMISSION IS GRANTED BY THE OWNER
AND THAT IT SHALL BE RETURNED UPON DEMAND.

REVISIONS	DATE	S	BY	APVD.

JCM

JCM INDUSTRIES, INC. NASH, TX.

P.O. BOX 1220
NASH, TX. 75569
www.jcmindustries.com

OFFICE: (903) 832-2581
TOLL FREE: (800) 527-8482
FAX: (800) 874-9524

440-30", 36" & 42" x24" T12 ESS

FLANGED OUTLET TAPPING SLEEVE - LINE STOP ACCURACY

UNLESS OTHERWISE SPECIFIED TOLERANCES TO BE			DRAWN BY	CHECKED BY	APVD. BY	DWG. NO.	REV.
FRACTIONS	DECIMALS	ANGLES	RTM	----	----	GEN-009698	---
± 1/4"	.125	2°	DATE	NO. SHEETS	SCALE	PART NO.	---
			01-02-14	1 of 1	----	----	